

INVENTOR

Jack MOOREHEAD
4370 La Jolla Village Drive; 4th Floor
San Diego, California 92122

Joseph T. LODICO
4370 La Jolla Village Drive; 4th Floor
San Diego, California 92122

The inventors are citizens of the United States

TITLE OF INVENTION

CHEMICAL REMOVAL AND SUSPENDED SOLIDS
SEPARATION PRE-TREATMENT SYSTEM

Attorney Docket No. MOORJ-02

MOORJ-02

TITLE

CHEMICAL REMOVAL AND SUSPENDED SOLIDS SEPARATION PRE-TREATMENT SYSTEM

CROSS REFERENCES TO RELATED APPLICATIONS

5
PAA
7/23/02
This application is a continuation-in-part to an application
now Pat. No. 6,932,980
filed on March 13, 2000, Application number 09/524,578.

STATEMENT REGARDING FEDERALLY-SPONSORED RESEARCH OR DEVELOPMENT

Not applicable.

FIELD OF THE INVENTION

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155

raw influent water before the water to be processed enters the treatment plant filtration system.

Proper water treatment and filtration are major concerns for the health and safety of all inhabitants where ever located.

5 Improper treatment and/or disposal causes health problems, disease, and even death. The Center for Disease Control (CDC), through DNA tests, identified human sewage as the source of the 1993 Milwaukee, Wisconsin, *Cryptosporidium parvum* parasite outbreak that infected over 400,000 people in that city. In the latest issue of the CDC's, Emerging Infectious Diseases Journal, the results are reported on the molecular analysis of 39 isolates of *Cryptosporidium parvum* from human and bovine sources in nine human outbreaks, including isolates from the 1993 Milwaukee outbreak. The new study suggests that the source of the parasite *Cryptosporidium parvum* in the Milwaukee outbreak is human, not bovine.

Four stool specimens were examined from the Milwaukee outbreak: three from the original outbreak and a fourth from an AIDS patient in 1996 who had initially been infected in the 1993 outbreak. All four were found only in isolates from humans. None of the four isolates were capable of producing an infection in laboratory animals.

Animal waste was also identified by DNA tests as the source of the Canadian *E. coli* outbreak that infected over 2,000 people

in Walkerton, Ontario, following a summer rainstorm in May 2000. A deadly strain of E. coli bacteria was distributed by the Walkerton, Ontario public water supply in May, killing six people and infecting 2,000 others. New Canadian regulations were passed forcing municipalities to ensure the water is safe and to thereby prevent any recurrence.

Canadian municipalities must release their first public water quality reports by October 30, 2000. Municipalities that violate the rules face fines ranging from \$20,000 to \$2 million. Jail sentences can also be imposed. This new regulation establishes tougher drinking water standards and policies that reflect the most current expertise and procedures in drinking water protection. Additionally, the U.S. Consumer Confidence Report requires every public water utility to distribute a detailed analysis of the chemicals, parasites, bacteria and virus in their public water supply for the previous year to all homeowners. These water quality reports are increasing the demand for better technology that works.

All public water districts using surface water must install filtration equipment and hire a State certified grade-3 plant operator by the year 2003, which is the Clean Water Act regulations deadline for small water districts. The largest immediate market for pre-filtration systems are in those states with the highest number of small water districts using surface water. Efficient and effective pre-filtration systems are a

mandated necessity under current regulations/requirements. The pre-filtration system of the present invention meets, and exceeds, the challenges imposed by these regulations/requirements and far surpasses current pre-filtration systems in that challenge.

Water supplies for domestic drinking water, process water for chemical plants, or other liquids are often contaminated with a variety of contaminants, such as, but not limited to, toxic chemicals, volatile chemical contaminants (such as MTBE, benzene, perchlorate, trihalomethanes, and the like), pesticides, particles such as algae, other suspended organic and inorganic solids, dissolved oils, and other particles including large and heavy particles and light, fine, or buoyant particles (referred to collectively as contaminants). These contaminants must be removed in a reliable and cost-effective, cost-efficient manner.

The pre-filtration water decontamination system of the present invention was designed to remove most of the organic suspended solids (such as, but not limited to, algae), and volatile toxic chemicals from the raw influent water before it enters a final-stage treatment plant filtration system. Pre-filtration is necessary for a more efficient operation of the final-stage filtration. Common pre-filtration systems include use of sand filters, membrane filters, chemical flocculation-sedimentation-filtration (settle-to-the-bottom method), and large tank-type dissolved air flotation (DAF) systems. These systems

and methods do work at pre-filtration but are not as effective nor as efficient as is necessary for proper pre-filtration.

Many older water treatment plants use gravitational separation methods, typically in sedimentation systems or dual-media sand filtration systems that may not be acceptable under the newer water quality standards. In some cases, these systems can meet the standards through the use of properly mixed polymer chemical filter aids. The required expensive and complex polymer chemical mixing equipment requires constant attention, since the amount of the chemicals being added to raw water must be frequently readjusted to match the continually changing chemistry of the water being filtered. Slow sand filters require a considerable investment, but generally can be operate for longer periods without cleaning. Unfortunately, even with pre-treatment, both dual-media and slow sand filters fail to meet water quality standards for hours or several days after each backwash cleaning. Ordinary sand filters become overwhelmed after every rainstorm. Membrane filters, which generally are more efficient than sand filters, quickly clog and require constant attention whenever it rains. The system of the present invention actually becomes more efficient when turbidity increases.

Ordinary chemical flocculation and sedimentation processes are slow, require chemicals, and their maintenance is high.

Moreover, they do not prevent toxic chemicals, pesticides and

algae from passing through the ordinary filter bed. If algae spores, for example, are present when chlorine is added, toxic disinfection byproducts are formed, which is highly undesirable and a violation of the USEPA Safe Drinking Water Act. The inability of older municipal filtrations systems to remove algae is apparent in the lack of clarity found when a swimming pool is filled with "clean" tap water. Most pool contractors have to shock tap water with large doses of chlorine chemical pool oxidizer to achieve the desired clear pool water appearance.

Some decontaminating systems, such as air stripping towers, currently discharge toxic chemical gases and volatile organic compounds into the atmosphere. Particulate material has also been removed from liquids by DAF floatation, another gravitational method, in which bubbles of a gas, such as air or oxygen, are introduced into the lower levels of the liquid and float to the top, carrying fine particles with them. These systems rely heavily on chemicals whereby chemical flocculates and microscopic air bubbles slowly float to the surface of a large flotation tank. This system is very costly and cumbersome requiring chemical mixers to blend flocculating chemicals such as alum (aluminum) with the raw influent before it enters a main tank. A large impeller pump injects high-pressure water containing excess dissolved air through an array of jet nozzles in the bottom of the tank. Mechanical scrapers push the float particles into a trough for removal and dewatering. These are

relatively inefficient, in light of the outbreaks above-described, costly to operate and maintain, and require proper treatment and/or dispose of chemical residues and by-products.

Flotation is a gravitational method because the rise of bubbles is due to the gravitational acceleration acting on the mass of the liquid in accordance with the basic force equals mass time acceleration relationship. A force balance relative to a pocket of gas phase within liquid (a bubble), where the mass of the bubble is its volume times its density, shows that the bubble must rise to find equilibrium, because the density of a gas is generally less than that of a liquid. Large flotation tanks are required to allow adequate time for air bubbles to reach the surface.

Failure to remove all contaminants prior to filtration also leads to clogged filters, increases filter operation costs and wastes water required for frequent filter cleaning cycles. The use of flocculation promoting chemicals increases the volume of sludge to be dewatered and removed.

Thus, there is a continuing need for a pre-filtration (or pretreatment) separation system that will rapidly, efficiently, and effectively remove particles and volatile gases from liquids while treating a liquid, will efficiently remove algae and volatile gases (all contaminants) during pretreatment prior to filtration and will reduce overall treatment costs and conserves

water through less frequent filter cleaning and a smaller sludge volume.

5 The present invention uses micro-bubbles with ionized ordinary ambient air (to form micro-bubbles) which basically blend with raw process water (raw influent). These micro-bubbles attach to suspended particles (contaminants) of the raw influent and are quickly removed from the water stream with a hydrocyclone vortex extraction column (separator). This extraction method is simple and environmentally friendly. No aluminum chemicals are used, which as a result reduces the volume of sludge to be disposed of in landfills. By simply removing most of the contaminants from the process water stream, the present invention prevents the formation of toxic chemical byproducts when necessary chlorine residuals are added to prevent bacterial regrowth in the community distribution system.

15 After removal of the contaminants, decontaminated water (which has been separated from the raw influent) is discharged to the filtration system and the waste water is discharged to a recovery system for recovery and removal of disposable and/or any recyclable waste (sludge) and re-processing of remaining waste water back through the system. This pre-filtration system was designed to remove contaminants from raw influent before it enters the treatment plant filtration system. it is simple, efficient, effective, low in maintenance, and environmentally friendly. No chemicals are used, which thereby reduces the

volume of sludge to be disposed of in landfills. Removing most of the contaminants from the raw influent prevents the formation of toxic chemical disinfection byproducts, formed when chlorine chemical residuals are added to other systems to prevent bacterial re-growth in community water distribution systems.

Accordingly, several objects and advantages of my invention are to:

a. establish a pre-filtration system which is low in cost, easy to install, and easy to maintain;

b. provide a pre-filtration system which is relatively compact in size;

c. dramatically reduced replacement costs for a pre-filtration system;

d. provide for a pre-filtration system which is extremely efficient in separating waste matter, solids and gases, from an influent stream;

e. to minimize or eliminate the use of chemicals and toxins in a pre-filtration system; and

f. more safely and effectively pre-treat influent.

The foregoing has outlined some of the more pertinent objects of the present invention. These objects should be construed to be merely illustrative of some of the more prominent features and applications of the intended invention. Many other beneficial results can be attained by applying the disclosed invention in a different manner or by modifying the invention

within the scope of the disclosure. Accordingly, other objects and a fuller understanding of the invention may be had by referring to the summary of the invention and the detailed description of the preferred embodiment in addition to the scope of the invention defined by the claims taken in conjunction with the accompanying drawings.

BRIEF SUMMARY OF THE INVENTION

The above-noted problems, among others, are overcome by the present invention. Briefly stated, the present invention contemplates a pre-filtration water decontamination apparatus having an oxygen saturator for introducing high-pressure air and a high-pressure ozone-treated ionized water mixture therein and to substantially saturate this high-pressure treated/ionized water mixture with excess oxygen thereby creating a high-pressure oxygenated mixture (HPOM) stream; a blender for receiving and mixing the HPOM stream from the oxygen saturator with influent water containing contaminants to be removed; means for directing the HPOM stream from the oxygen saturator, at a pre-determined pressure, to the blender, and means for directing influent water to the blender at a lower pressure such that a white-water process (WWP) stream comprising a plurality of micro-bubbles is created in the blender; a separator for receiving the WWP stream from the blender and having means for causing upward vortex rotation of the WWP stream, for separating from the WWP stream a

waste water stream along a central axis of the upward vortex of the separator, and for separating from the WWP stream a decontaminated water (DCW) stream along an outer wall of the separator; and a recovery unit for directing discharge of the DCW stream out of the apparatus through a water outlet, and for directing disposition of the waste water stream out of the apparatus for re-processing and for recycling.

The foregoing has outlined the more pertinent and important features of the present invention in order that the detailed description of the invention that follows may be better understood so the present contributions to the art may be more fully appreciated. Additional features of the present invention will be described hereinafter which form the subject of the claims. It should be appreciated by those skilled in the art that the conception and the disclosed specific embodiment may be readily utilized as a basis for modifying or designing other structures and methods for carrying out the same purposes of the present invention. It also should be realized by those skilled in the art that such equivalent constructions and methods do not depart from the spirit and scope of the inventions as set forth in the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Details of the invention, and of preferred embodiments thereof, will be further understood upon reference to the drawings, wherein:

Figures 1A and 1B represent a flow chart of the pre-filtration decontamination system;

Figure 2 is a top plan view of the system.

Figure 3 is a exploded perspective view of the oxygen saturator;

Figure 4 is detailed view of the file support screen of the holding assembly.

Figure 5 is detailed view of one section of the flow distributor.

Figure 6 is an exploded perspective view of the blender.

Figure 7 detailed perspective and partially cut-away view of the separator and recovery unit combination.

DETAILED DESCRIPTION OF THE INVENTION

A flow chart for the pre-filtration water decontamination system of this invention is provided in Figures 1A and 1B. Ambient air enters a conventional oxygen concentrator and air dryer 12 where oxygen is concentrated from, for example, a resin nitrogen chemical adsorption process. A typical oxygen concentrator, or its equivalent, is Model/Part Number PPTitan/16 distributed by Ozotech, Inc., of Yreka, California. The oxygen

concentrator 12 increases the proportion of oxygen in the air to about 60 to 96 per cent.

Next the concentrated oxygen enters a conventional corona discharge type ozone generator 14 where a suitable percentage of the oxygen is converted to ozone. A typical such generator, or its equivalent, is Model/Part Number OZ2BTU distributed by Ozotech, Inc., of Yreka, California. The resulting oxygen-ozone gas mixture is drawn into a water tank 11 by a venturi 17 where it is dissolved and blended with clean water from the water tank 11 through the venturi 17 by a pump 18 (a conventional impeller pump for example). The water, with dissolved ozone, in the water tank 11 is now ionized or positively charged. It receives 'clean' water (also referred to as re-circulated water or tap water; i.e., already processed through a full filtration system). The water tank 11 has a conventional level sensor or float valve 13 to detect the level of water therein and to cause the water tank 11 to be refilled as needed. A conventional ozone sensor in the water tank 11 monitors the ozone concentrations therein.

A conventional hi-pressure pump 20 draws the ionized, ozone-treated water from the water tank 11 and, at high pressure, injects it into an oxygen saturator 31. A conventional solenoid-actuated air valve 27 adds additional air when the air envelope inside the oxygen saturator 31 shrinks as it is being adsorbed. Output is measured by the flow meter 30. The preferred pressure

is between about 80 psi and 150 psi with 120 psi being optimal. An air relief valve 28 dispels excessive pressure build-up to prevent damage to the oxygen saturator 31. The oxygen saturator 31 cause the high-pressure air to create a high-pressure mixture which flows through the oxygen saturator 31 whereby excess dissolved oxygen, nitrogen, and other gases present in the ambient air from the air compressor are adsorbed. The resulting water stream is referred to herein as a high-pressure oxygenated water mixture (HPOM) stream.

Sub 61
The HPOM (designated by flow arrow X in Figure 1B) is discharged into a blender 51 at between about 80-150 psi; with 120 psi being optimal where it is blended (mixed with) incoming raw influent. Raw influent is drawn into the blender 51 at a pressure significantly less than the pressure of the HPOM by a conventional disk suction pump 61. The preferred pressure is zero to negative for the raw influent; with negative pressure being optimal. When the HPOM comes into contact with the lower pressure / negative pressure created by the drawing-in of the raw influent, because of the significant degree of pressure difference, the HPOM stream turns to white-water (countless numbers of dense, opaque micro-bubbles) and immediately blends or broadcasts into the raw influent. The white-water is injected through the jet inlets or nozzles 53 around the perimeter of the inner wall 64 of the mixing chamber 60 to thereby blend with the raw influent stream. The ionized white-water micro-bubbles blend

with the negatively-charged organic contaminants to form large buoyant clusters of micro-bubble-coated organic particles. The resulting stream herein (consisting of the HPOM white-water and raw influent) is referred to as a white-water process (WWP) stream.

The WWP stream is discharged (as designated by flow arrow Y in Figure 1B), via a tangential port 72, into the base of a hydrocyclone separator or separator where, because of the centrifugal rotation create an upward vortex column therein with high-pressure at the outer perimeter of the separator and lower pressures at the center of the vortex column. The divergent pressures of the WWP stream causes waste, which is covered with micro-bubbles, to separate from the WWP stream and further coalesce at the center (referred to as the waste water stream) and, thereby, causes clean or decontaminated water to separate from the remaining WWP stream at the high pressure perimeter (the decontaminated water is referred to as the DCW stream). The DCW stream is relatively clear and the waste water stream bears the color characteristics of the waste contaminants therein. Heavy and/or larger contaminants may be deposited into a sump 73 at the bottom of the separator and are drained therefrom at the drain port 74.

At the top of the separator 71 a waste outlet discharges the waste water stream (as designated by flow arrow Z in Figure 1B) and a water outlet, below the waste outlet, discharges the DCW

stream (as designated by flow arrow A in Figure 1B) as the clean
water output 84. The DCW stream is monitored and regulated by a
flow meter 80. The DCW is then conveyed to the main filtration
system (as designated by flow arrow A' in Figure 1B). The waste
5 water stream collects at, and is further processed in, the waste
removal and collection unit 91 (or recovery unit). Here,
recyclable waste or sludge is captured in a waste filter 90 and,
after the filter is partially full or completely full, the
collected waste is dispensed to a waste hopper 111 or equivalent
10 collection unit (as designated by flow arrow C in Figure 1B) for
further disposition and/or recycling after collection of a pre-
determined quantity (as designated by flow arrow C' in Figure
1B). Waste water processed through the recovery unit 91 is
returned to the blender 51 for further processing (as designated
15 by flow arrow B in Figure 1B).

The entire system is programmed with conventional software
and monitored and controlled by one or more nodes (tank node 19,
saturator node 49, and separator node 79 as illustrated in
Figures 1A & B) for proper pressures (by conventional pressure
20 sensors 16 where needed as illustrated in Figures 1A & B), for
proper electrical current (by conventional current sensors 15
where needed as illustrated in Figures 1A & B) necessary to
activate, as needed, the various pumps (ionized water tank pump
18, high pressure pump 20, disk suction pump 61), stream flow
25 (flow meter 30 for the high-pressure pump 20, flow meter 80 for

the clean water flow), the various valves (for the oxygen saturator 31, the blender 51, the separator 71, and the waste removal and collection system [recovery unit] 91 to receive or to discharge a respective stream and or build-up of gases or pressure), motors 67 and drives 68, level sensors 21.

Typical products, or their equivalent, include for the nodes, Model/Part Number EC230 distributed by CNA Engineers, Singapore; for the pressure sensors, Model/Part Number MSP600-250-P-5-D-4 distributed by Measurement Specialities, Inc., of Valley Forge, Pennsylvania; for current sensors, Model/Part Number HA 10-NP, LTS 25-NP, HY 50-P, or HAL 50-S distributed by LEM USA, Inc., of Milwaukee, Wisconsin; for the high-pressure pump, Model/Part Number 10GBC20 distributed by Barrett Pump of San Diego, California; for the air compressor, Model/Part Number Emgio 283MK 15A8P distributed by White Cap of San Diego, California; for the flow meters, Model/Part Number V2-M1-A300F300-E3-X1-25 or V2-M1-A100F50-E3-X1-25 distributed by Asahi-America of Malden, Massachusetts; for the valves, Model/Part Number 509F distributed by Inline Industries; and for the valve actuators, Model/Part Number 509-20S8-3LA-TRIM-01 distributed by Bettis Actuators and Controls.

The entire process is controlled by a conventional communication hardware and software. The protocol used in the present invention is an Echelon LonWorks® digital network; though any equivalent communication hardware and software suited for the

intended purpose will suffice. The control software programs are distributed among the various control nodes 19, 49, 79 which monitor and control specific treatment processes within this pre-filtration decontamination system. All actions, such as but not limited to, actuating valving, monitoring and altering pressures, monitoring and altering electric current, starting and stopping the various pumps, monitoring the various air envelopes and water levels, starting and stopping the various motors, and starting and stopping the various compressors, are controlled by these nodes and the respective hardware and software interfacing with and connected to the decontamination system. These monitoring and control equipment and components work together intelligently on a single LonWorks® digital network and can be monitored, controlled, and managed over the Internet. The system of the present invention may be turned on/off automatically by the software; may be turned on/off automatically independent of the software; or may be turned on/off manually; or any combination thereof.

The pre-filtration water decontamination system and apparatus, as represented in Figures 1A&B and Figure 2 by reference character 10, encompasses the water tank 11 and ozone generator 15 combinations, the oxygen saturator 31, the blender 51, the separator 71, and the recovery unit 91. Reference now should be made to Figures 3 through 5. As described above, high-pressure oxygenated ionized water saturated with dissolved ozone

from a corona-discharge ozone generator 14 is injected under high pressure from the ionized water tank 11 into the oxygen saturator 31 through the saturator inlet port 32. The pressure (from about 80-150 psi; 120 psi optimum) forces this high-pressure water stream into the oxygen saturator up to the top through the saturator intake pipe 33 where a flow distributor 40 thereat evenly distributes the high-pressure water stream into the saturator chamber 42. Holding assemblies 35, near to the top and the bottom of the saturator chamber 42 securely hold suitable fill material 39 within the saturator chamber 42. The upper and lower holding assemblies hold the fill material 39 in place with mesh-like material therein to thereby permit the flow of the high-pressure water stream therethrough.

The high-pressure water stream percolates down through packed fill material 39 in an envelope of high-pressure air and out of the oxygen saturator through the saturator exit port 44. Conventional sensor assemblies 21 (such as ultrasonic level sensors) control the volume of the high-pressure water stream and the high-pressure air envelope. The sensor assembly 21 is in communication with the saturator chamber 42 and detects the water level and the air pressure therein. The sensor assembly 21 is generally located above the saturator exit port 44.

The sensor assembly 21 can be any conventional sensing unit suited for the intended purpose. Typical sensor assemblies

include Model/Part Number LVU-152 distributed by Omega of Stamford, Connecticut, or its equivalent.

Such sensor assemblies 21 are adapted to monitor various water levels and air pressure and based on the levels thereat and

5 the location of the sensor assembly 21, to detect the need for air valves to open and/or close, to detect the need for water valves to open and/or close, and to detect the need for a water stream and/or air, as the case may be, to enter or to be

discharged. Each sensor assembly 21 has a high-level sensor 22

10 with a probe 24 and a low-level sensor 23 with a probe 25 and

may, but need not, have an air valve for the purpose of releasing excess or unwanted air and/or gases. The function of each sensor assembly, though similar, differs somewhat based on its location; i.e., whether associated with the oxygen saturator 31 or with the separator 71 (and recovery unit 91)

15 The high-pressure water stream becomes saturated with excess oxygen in this environment and under these conditions. When the air envelop 'shrinks' as it is adsorbed by ionized ozone-treated water cascading through the fill material 39, the sensor assembly
20 21 energizes a compressed-air line valve to replenish the high-pressure air adsorbed by the high-pressure water stream. The pressure maintained in the oxygen saturator should be between about 80-150 psi; with 120 psi being the optimal pressure for the best results.

The flow distributor 40 is a unique feature of the oxygen saturator 31. It is located adjacent to the top of the oxygen saturator 31 above the upper holding assembly 35. At its center is an aperture 46 for entry of the high-pressure water stream from the saturator intake pipe 33. Radiating from the center are a plurality of spokes or fingers 45 of varying lengths. These fingers 45 are basically flat surfaces having at the distal ends, a slot 43. One finger 45 and one slot 43 is a finger/slot set. The flow distributor 40 may have one or more finger/slot sets for a section 41. A wall or raised ridge 47 may, but need not be between each finger/slot set. I have found that between six to 14 such finger/slot sets will function well. In addition, the flow distributor 40 may have one or more sections 41 of such finger/slot sets. Good results are obtained with about four to 12 sections 41 bearing between about six to 14 finger/slot sets; although more or less of either (section or set) will also suffice. Best results are obtained with about eight sections bearing between about nine to 11 finger/slot sets.

Additionally, where each section 41 contains a plurality of finger/slot sets, for best flow distribution, I have found that the slot 43 of each succeeding finger 45 should be larger than the slot 43 of the previous finger 45 until the final slot 43 has no finger 45 or the finger 45 is merely a stub. In other words, the first finger 45 to a section 41 of a finger/slot set may have a small slot 43 (or slit) or none at all. The next finger 45 of

a finger/slot set has a larger slot 43 and so on in the same direction. When the finger 45 of the last finger/slot set of a section 41 is a stub or none at all (approximately a near-full slot or a full slot), the next section 41 begins.

5 The functionality of the flow distributor 40 cannot be understated. With the relatively flat fingers 45 a water stream flows evenly over the flat fingers 45 and up to and out of the slot 43. The length of the slot 43 for each succeeding finger 45 becomes larger and larger. The water stream flows into the
10 smallest distal slot 43 near to the outer perimeter of the saturator chamber 42 and incrementally, with the adjacent slots 43, nearer and near to the center; repeatedly for each succeeding flow section 41. A even distribution of the high-pressure water stream is fed into the saturator chamber 42 for a more efficient
15 saturation effect. Conventional nozzles or jets will become plugged or clogged with various contaminants, such as, but not limited to slime, scale, and calcium. They will then require cleaning; this will take time resulting in down-time for the pre-filtration process. With the flow distributor 40 of the present
20 invention, any build-up occurs on the flat surfaces of the fingers 45, and only at the drop-off edge of the slots 43. The water stream is relatively unimpeded and, over time, when an obstructing build-up does occur, maintenance is simple. The saturator cap 36 and flow distributor 40 are easily removed. The
25 offending contaminants then may simply be scraped off, dissolved

with acid or its equivalent, or replaced with a new flow distributor 40. In either event, disruption of use of the oxygen saturator 31, and effect on the entire system, is minimized.

After the high-pressure water stream (which includes high-pressure ionized ozone-treated water mixture) is fully oxygen-saturated (containing excess dissolved oxygen; approximately 50-90 mg/l) it exits the oxygen saturator 31 from the saturator exit port 44. This mixture stream, referred to as an HPOM stream, exits the oxygen saturator 31 at a high pressure as described above.

Reference is now made to Figure 6. As the HPOM stream is forced into the blender 51 through the blender inlet port 52, raw influent is brought into the blender 51 through the raw influent inlet port 62; at a significantly lower pressure than the pressure of the HPOM stream (preferably at zero to negative pressure). The effect is created by the disk suction pump 61 which draws the raw influent into the blender 51. This disk suction pump 61 is a conventional vacuum pump such as Model/Part Number 215T CP3768T-4 402-12 provided by the DISCFLO Corporation of San Diego, California or its equivalent.

The disk pump 61 is not like a centrifugal pump, positive displacement gear, or lobe pump. It is a boundary-layer viscous-drag vacuum pump that draws in the raw influent and in the process discharges the WWP stream from the blender 61 into the separator 71 at high velocity with minimum shear, and virtually

no turbulence. The disk pump 61 has a series of parallel rotating smooth-surface disks to create a boundary layer viscous drag force that pulls the WWP stream through the pump housing without turbulence.

5 Other pumps use some type of impingement device, relying on force to push the water through the pump. Ordinary impeller pumps shear the polar bond of the micro-bubbles and the formed and forming clusters of particles (contaminants) and micro-bubbles. This causes the micro-bubbles to separate from the
10 microscopic solid particles of the raw influent before they can be discharged to the separator. The non-impingement and laminar flow of the disk pump 61 is similar to the flow through an ordinary pipe. The layer of fluid at the disk surface is stationary (relative to the rotating disks), moving faster than the layers in the middle between the disks, creating a boundary layer drag effect. Viscous drag pulls the boundary layers into multiple smooth laminar flow streams.

15 A micro-bubble's polar bond with the microscopic solid particles of the raw influent particles will separate if exposed to
20 excessive pump shear forces. The smooth laminar flow feature prevents that from occurring and is essential to this process.

25 Additionally, disk pumps actually perform more efficiently when pumping algae-laden water. Water containing dense concentrations of algae will cling more readily to the disk surface, which increases disk pump flow rates. The variable

speed controller for the motor 67, 68 of the disk pump is connected to an ultrasonic flow meter and a vacuum sensor 57, which automatically adjusts the speed of the motor 67 of the disk pump 61 to maintain a constant, pre-determined gallon-per-minute (GPM) flow rate, regardless of viscosity or turbidity of the stream being processed. As a result, the pre-filtration system of the present invention becomes more efficient and consumes less electrical energy during a rainstorm.

The viscous-drag of the smooth surfaces of the disk pump 61 form boundary layers, which draw raw influent into and through the blender 51. The raw influent, under negative to zero pressure, is drawn into the blender mixing chamber 60 through a plurality of radiating blender inlet slots 63 interspaced between blender inlet spokes 65. At the same time, the HPOM stream enters the blender mixing chamber 60, from the blender intake chamber 50, through a plurality of blender nozzles 53 located above, and in alignment with, the blender inlet slots 63. When the HPOM stream, saturated with excess dissolved oxygen, enters the mixing chamber 60 it immediately reacts to the substantially lower pressure therein by forming into a plurality of ionized micro-bubbles. This is a phenomenon known as white-water. The white-water immediately broadcasts throughout and blends with the raw influent turning the entire mixture opaque. This resultant white-water mixture stream is referred to herein as the white-water process (WWP) stream.

With regard to the white-water phenomenon, as the HPOM stream (which contains excess dissolved oxygen) is injected into a low-pressure environment, the excess dissolved oxygen immediately expands to form billions of "invisible" micro-bubbles (over 400 million microscopic air bubbles per gallon). The total surface area of the micro-bubbles within one-gallon of white-water is approximately 250,000 square feet. The oxygen inside the micro-bubbles refracts white on the color scale, giving the opaque raw influent a chalk-white appearance, which is why the result is called "white-water." The ratio of the HPOM stream, and its white-water, to that of raw influent to create a overall white-water effect (of the HPOM stream and raw influent) is about 10% to 15% HPOM stream to the raw influent.

Additionally, air bubbles in the range of a one-micron diameter (or smaller) have little buoyancy and will remain stationary unless external forces are applied to them. Microscopic solid particles (contaminants in the raw influent) also remain stationary in water and rarely collide with adjacent micro-bubbles unless there is a polar attraction. Micro-bubbles which do collide with other adjacent micro-bubbles form increasingly larger bubbles, which eventually become sufficiently buoyant to slowly rise to the surface (this is the process used for a tank-type DAF floatation system and is precisely why very large dissolved-air flotation tanks are required for its process).

If, however, the micro-bubbles are ionized (as in the system and apparatus of the present invention), hundreds of positively charged micro-bubbles will attach themselves to the negatively charged microscopic solid particles (contaminants) contained within the raw influent thereby coating the contaminants and creating numerous multi-micro-bubble combinations (containing the contaminants) in the process. These newly formed multi-micro-bubble combinations then collide with, and attach to, each other thereby forming increasingly larger clusters upon clusters of such combinations. These newly formed larger clusters become buoyant and will begin to rise slowly to the surface. As these larger clusters so rise they collide with, and attach to, other similar large clusters, thereby increasing in size and in buoyancy in the process. The attaching process repeats and repeats throughout the process and the buoyancy of the clusters increases with their size.

The plurality of blender inlet slots 63 are basically around the perimeter in the base or floor 58 of the blender mixing chamber 60. Each blender inlet slot 63 has a corresponding nozzle 53 located directly above each blender inlet slot 63. This facilitates mixing of the raw influent with the HPOM stream by causing the raw influent to pass directly up to each nozzle 53. Turbulence of mixing may be enhanced by adding dimples 55 on the inner surfaces of the wall of the blender 51. Increased mild turbulence cause more of a grouping or clustering effect.

The WWP stream fills the blender 51 quickly and discharges from the blender exit port 54 into the separator 71 (Figure 7) by way of the separator inlet port 72 (preferably an angled or tangential port). The blender cap 66 maintains the WWP stream within the blender 51 and, thereby, forces the WWP stream out of the blender 51. The blender cap 66 is removable to facilitate maintenance of the blender 51 and its nozzles 53 and blender inlet slots 63 as needed. Since there are no moving parts, maintenance is minimal.

The WWP stream enters the separator 71 from the blender exit port 54 via the separator inlet port 72. This separator inlet port 72 (preferably an angled or tangential port) located in the lower section 78 of the separator 71. The separator 71 basically consists of a lower section 78, a central section 77, and an upper section 76. It may be tubular but preferably is hour-glass shaped with the central section 77 narrower than the upper and lower sections 76, 78. The preferred embodiment is that of an hour-glass shape. It may be formed from a transparent material such as glass or an acrylic resin to permit observation of the flow therethrough.

By this configuration, an upward vortex column (or vortex column) is created and laminar viscous-drag separation is achieved in the process. In this regard, when the WWP stream (high-pressure water containing excess dissolved oxygen blended into the raw influent stream) is subjected to centrifugal forces

inside a separator 71 of rapidly spinning water effected by the tangential angle of the separator inlet port 72, it causes the WWP stream to rotate and flow upward. As the spinning column of the WWP stream reaches the narrow central section 77 of the separator 71, the velocity of the vortex column markedly increases, creating a high-pressure zone at the outer perimeter of the separator 71 and a low-pressure zone in the center of the vortex column. The now buoyant micro-bubbles attached to the microscopic solid particles (as well as their forming and formed combinations and clusters) are forced into the center of the vortex column by the viscous drag of the laminar transfer process. This is caused as water molecules drag across the surface of the perimeter wall of the separator 71, they will tend to slow down and move at a slower pace than water molecules away from the surface wall. The next inner layer of molecules moves at a slightly faster rate. Each subsequent layer of water molecules moves even faster and causes or contributes to the diminishing viscous drag of each succeeding (or laminar) layer. This is called laminar flow, where the velocity of the water is slower at the perimeter and accelerates in the center of the separator resulting in the transfer process.

Unlike a large, deep flotation tank as in the prior art, the distance between the outer perimeter and the center of the vortex column in the separator 71 is relatively slight; as slight as several inches. In this environment, micro-bubble/particle

clusters have a much shorter distance to travel (from perimeter to center) through the laminar layers of water molecules.

Laminar drag forces accelerate the movement or transfer of the water molecules (micro-bubbles, clusters, and combinations) towards the center of the vortex column. The viscous drag between each layer of spinning water molecules inside the separator 71 causes the micro-bubbles therein to elongate. The difference in the viscous drag on each side of the elongated micro-bubble (and combinations) pulls micro-bubbles from one microscopic laminar layer toward the center to the next microscopic layer, until they reach the center of the vortex column.

The low pressure at the center of the vortex column causes the microscopic solid particles (contaminants) of the WWP stream to coalesce in the center as the waste water stream. The high pressure at the perimeter of the separator 71 attracts the WWP stream, as cleansed of the waste water stream, thereby creating a decontaminated water (DCW) stream. The DCW stream is carried up the separator 71 and is discharged therefrom via the water outlet 84 (preferably an angled or tangential port) for final-stage filtration. This outlet has an upper inner edge 82 and a lower inner edge 83.

The waste water stream is carried to the top of the separator 71 by the spinning low-pressure center of the vortex column where it begins to accumulate. As gases from the waste

water also accumulate thereat forming an air pocket, the pressure from the gases forces the waste water level 85 to drop. A sensor assembly 21 (similar to the ultrasonic water level sensor previously described), which monitors and controls the waste water level, is attached in the upper section 76 of the separator 71. The waste water outlet 94 here has an top inner edge 92 and a bottom inner edge 93. When the waste water level 85 reaches the bottom inner edge 93 of the waste outlet 94, the actuator attached to the air relief valve 96 is energized to vent the excess accumulated gases through the carbon filter 98 and out of the system (as illustrated in Figure 7). It must be understood, however, that the configuration may be reversed with the air relief valve 96 being proximal to the sensor assembly 21 and the carbon filter 98 being distal to the sensor assembly 21. The carbon filter 98 captures the volatile toxic chemical gases and volatile organic compounds which were striped from the contaminated raw influent by the micro-bubble clusters as the waste water stream was created. The air pocket expands and the waste water level 85 drops.

Prior art air stripping towers currently discharge toxic chemical gases and volatile organic compounds into the atmosphere. When the carbon filter 98 is fully saturated, it is easily replaced. This venting also causes the waste water level 85 to rise again up, or near, to the top inner edge 92 of the waste outlet 94. The action is repeated as necessary and

prevents the waste water level 85 from contacting the upper inner edge 82 of the water outlet 84 which, should this occur, would deposit sludge or waste float thereat.

The recovery unit 91 additionally monitors and controls further disposition of the waste water stream. It has a plurality of valves 101, 102, 103, 104, and 105 which are activated to an open or closed position as needed. In the flushing mode, the waste water stream is periodically flushed into and through a sludge or waste filter 90. This is a conventional waste filter or screen adapted to separate solids from the waste water stream. For this mode, valve 101 (the main waste water valve) and the valve 104 (the filtered waste water valve) are opened--the waste filter 90 is positioned in between these two valves. The waste water stream passes through valve 101, into and through the sludge filter 90 for collecting the solids in the waste water stream, and out valve 104 returning this filtered or processed influent to the blender 51 for additional processing. When the sludge filter 90 is full, the recovery unit 91 initiates the recycle mode by closing valves 101 and 104 and opening valves 105 (the high-pressure air valve) and 102 (the waste hopper valve). High-pressure air (or any other suitable purging/cleansing liquid, material, or compound) enters the recovery unit 91 through valve 105 and flushes the collected waste sludge from the waste filter 90 and out valve 102 into a waste hopper 111. The sludge is held at the waste hopper 111

where it is processed for recycling or removal. Processing may be, but is not limited to, drying and packaging at pre-determined quantities.

After the waste filter 90 has been flushed of its accumulated sludge, valve 102 and 105 are closed. Periodic cleaning cycles back-flush the waste filter 90 cleansing it of remaining contaminants. In this regard, valve 103 (high-pressure water valve) and valve 104 are opened. High-pressure water (or any other suitable purging/cleansing liquid, material, or compound) from valve 103 passes into (direction arrow V) and through the waste filter 90 cleaning it of most, if not all, of any remaining waste particulants therein. The now contaminated high-pressure water passes through valve 104 and to the blender 51 for processing. The waste sludge is collected in a hopper for removal and disposal. Algae that is free of other contaminants is removed from the waste filter 90 can be packaged and sold as an animal feed supplement or fertilizer.

At this point, the water generally has had nearly all contaminants removed and can be passed to a conventional water plant filtration system via output pipe to remove any remaining particles. This pre-filtration process removes between 80.0-99.999% (5-log) of the suspended solids from the treatment plant process water flow; most regularly, such removal normally ranges above 99.99% (4-log). Also, substantially all algae is removed.

This is sufficient to meet present US EPA Clean Water Act regulations for a minimum 85% removal of suspended solids.

The operation, by volume and time, of the system described herein, under the examples set forth below, not as limitations to the present invention, would be as follows. Where the total volume of space between the upper ultrasonic-sensor and the lower ultrasonic-sensor inside the top of the separator column is 105.7 in.³, or 0.454 gallons of fluid wastewater; and where the volume of expanded oxygen adsorbed by the oxygen saturator 31 as dissolved oxygen adsorption of 80 mg/l (ppm) of excess dissolved oxygen at 120 PSI in a 10 GPM high-pressure fluid stream would be equal to 105.7 in.³ when fully expanded as one-micron sized white water micro-bubbles of white water inside the negative pressure of the blender 51 created by the vacuum disk pump 61. Therefore, under this setting, by way of example only, not by way of limitation, the total volume of air accumulating in the space between the lower 23 and upper 22 ultrasonic sensors at the top of the separator 71 per minute must be vented approximately once every minute. A 100-GPM flow rate and positive pressure inside the separator 71 will purge the 105.7 in.³ of accumulated air in approximately less than 1.5 seconds through the air relief valve 96. A higher system head loss will increase the air-purging rate. As to the rate of waste water (*i.e.*, buoyant suspended solids) accumulating at the top of the separator 71, a total of

400 mg/l (ppm) as algae and/or other buoyant suspended solids in the raw influent stream would be equal to about 0.04 gallons per minute. To fill half of the 105.7 in.³ volume (half of the 0.454 gallons) with suspended solids in the waste water collection area of the separator 71 (i.e., the waste water level 85), it would take approximately 5.675 minutes, or five minutes and 41 seconds. Assuming a waste water discharge rate of 20 GPM, the main waste water valve 101 and the filtered waste water valve 104 would be opened for approximately 1.4 seconds every 5 minutes to purge the waste water collection area 85 at the top of the separator 71.

Also by way of example only, not by way of limitation, a 400 mg/l (ppm) concentration of buoyant suspended solids in a 100 GPM raw influent stream flow would be equal to approximately 0.2 pounds of suspended solid waste every hour, or 0.0267 ft.³ of waste material per hour, or 46.14 cubic inches. Using a waste filter 90 with and 3.5 inch inside diameter by 16 inches high, the volume inside half of such filter would be approximately 76.97 cubic inches. Given the flow described above, this filter would become half full within approximately 36 minutes. As described herein, the various modes and cycles of the recovery unit 91 include: venting accumulated air in the top of the separator 71; discharging accumulated waste water from the top the separator 71 into the recovery unit 91 and through the waste filter 90; forcing the accumulated solid waste collected in the

waste filter 90 therefrom and into the sludge hopper 111; and, cleaning the waste filter 90. Under these general conditions, the system nodes would direct the following: the air relief valve in the top of the separator 71 will open for 1.5 seconds every minute; the recovery unit 91 will purge a volume of fluid equal to twice the amount of accumulated buoyant suspended solids from the top of the separator 71 approximately every five minutes, purging for about 1.4 seconds; the solid waste collected in the waste filter 90 generally would be emptied approximately every 36 minutes into the waste hopper 111; and the waste filter 90 would be cleaned (back flushed) once approximately every 24 hours, flushing for about one minute. All of the waste water is recovered and recycled.

The above example reflects only that based on contaminant concentrations, volumes, and desired results. The results can easily be varied by the software based on the contaminant concentrations and types, and volumes being received or desired.

It must also be understood that the apparatus and its components parts may be constructed of any material suited for the intended purpose. Preferably from materials approved and acceptable for potable water by the National Sanitation Foundation (NSF). Such materials included, but are not limited to, plastics, machined metal, cast metal, or the equivalents, or any combinations thereof.

The present disclosure includes that contained in the present claims as well as that of the foregoing description. Although this invention has been described in its preferred forms with a certain degree of particularity, it is understood that the present disclosure of the preferred form has been made only by way of example and numerous changes in the details of construction and combination and arrangement of parts and method steps may be resorted to without departing from the spirit and scope of the invention. Accordingly, the scope of the invention should be determined not by the embodiment[s] illustrated, but by the appended claims and their legal equivalents.

The invention claimed is: